
K-S-BKR M ENTL ABSCHL

Safety ball valves lockable, with relief port



Properties				
Operating pressure	Max. 10 bar			
Operating temperature	-20 °C to max. +100 °C			
Relief port	M 5			
Thread description	Rp thread acc. to ISO 7-1			
Hand lever	Stainless steel - PVC coated			
Ball seals	PTFE / NBR			
Stem seal	PTFE			
Material	Stainless steel			





Note

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Further information on request

Description

2/2-way stainless steel safety ball valves. Specially designed for pneumatic applications. The ball valve can be locked manually and has a relief port.

Additional information

The price does not include a padlock. Please order separately.

Item						
Identification	DN	Thread	Α (1111)	B	L	
K- 07 30 15 16	8	Rp 1/4	(mm) 100,0	(mm) 50,0	(mm) 55,0	
K- 07 30 15 17	10	Rp 3/8	100,0	50,0	55,0	
K- 07 30 15 18	15	Rp 1/2	130,0	60,0	65,0	
K- 07 30 15 19	20	Rp 3/4	130,0	64,0	74,6	
K- 07 30 15 20	25	Rp 1	165,0	71,0	88,0	
K- 07 30 15 21	32	Rp 1 1/4	165,0	78,0	102,0	
K- 07 30 15 22	40	Rp 1 1/2	190,0	86,0	110,0	
K- 07 30 15 23	50	Rp 2	190,0	95,0	125,0	

Accessories

K-VORHAENGESCHLOSS Padlock