
## K-WTST SAFETY BK SCHA AN DR HANSA

SAFETY service unit sets, comprising a ball valve with silencer, startup valve and pressure regulator



Properties	
Input pressure	2.5 - 16 bar
Output pressure	0.5 - 8 bar
Temp. range	-10 °C to +50 °C
Media	Compressed air
Sealant	NBR
Connection thread	Material: Die-cast zinc
Container	Polycarbonate (with bayonet lock) and bowl guard
Filter element	Cellpor (PE) 5 µm
Housing	Material: Grivory® (PA 66)
Diaphragm	NBR
Internal air consumption	Max. 1.5 l/min (depending on secondary pressure)
Flow rate measurement	At P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p$ = 1 bar
connection venting ball valve	Silencer





## Note

Further information on request

## **Description**

These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

## Ordering information

The price does not include a key lock and padlock. Please order separately. For accessories and spare parts, refer to individual components: ball valve, start-up valve, pressure regulator, filter regulator, 2-piece service unit

Identification	Thread	Control range	Flow rate	Α	В	С
		o o na o na ngo	(L/min)	(mm)		(mm)
K- 07 25 15 20	G 1/4	2.5 - 8 bar	2000	156,0	128.5 mm	95,5
K- 07 25 15 21	G 3/8	2.5 - 8 bar	2000	156,0	128.5 mm	95,5
K- 07 25 15 22	G 3/8	2.5 - 8 bar	4300	189,0	149.5 mm	110,0
K- 07 25 15 23	G 1/2	2.5 - 8 bar	4300	189,0	149.5 mm	110,0
K- 07 25 15 24	G 3/4	2.5 - 8 bar	10000	255,0	191.0 mm	137,0
K- 07 25 15 25	G 1	2.5 - 8 bar	10000	255,0	191.0 mm	137,0

Accessories	
K-STECKSCHLOSS	Key lock
K-VORHAENGESCHLOSS	Padlock