


K-DRG DRV 250 NIEDERDRUCK

DRV 250 pressure regulators, low-pressure type



Properties	
Input pressure	Max. 25 bar (Series 200 and 300 Series), Max. 40 bar (400 Series)
Temp. range	Max. 75 °C
Reduction ratio	Max. 10:1 (200 Series), Max. 20:1 (300 Series), Max. 6:1 (400 Series)
Sealant	NBR
Spring bonnet	Pressed brass up to DN 25, Grey cast iron from DN 32
Housing	Red brass 2.1096.01



Note

Further information on request

Description

Diaphragm pressure regulators with non-self-relieving design and non-pressure-reduced single-seated valve. Very precise adjustment. Good response characteristic because of only a few moving parts which hence minimal friction. Ideal for compressed air, nitrogen and other neutral, non-flammable gases, but only suitable for liquids with comparatively low flow rates.

Ordering information

Other designs available on request

Additional information

Other designs available on request

Item							
Identification	Thread	Control range	flow kvs-value (m ³ /h)	A (mm)	B	C (mm)	D (mm)
K- 07 25 04 94	G 1/4	0.2 - 2 bar	0,5	70,0	185.5 mm	140,0	45,5
K- 07 25 04 95	G 3/8	0.2 - 2 bar	0,6	70,0	185.5 mm	140,0	45,5
K- 07 25 04 96	G 1/2	0.2 - 2 bar	1,2	85,0	232.5 mm	186,0	46,5

Spare parts

K-VERSCHLEI-SATZ	Set of wearing parts
------------------	----------------------