
K-DRG DRV 250 NIEDERDRUCK

DRV 250 pressure regulators, low-pressure type



| Properties | |
|-----------------|---|
| Input pressure | Max. 25 bar (Series 200 and 300 Series), Max. 40 bar (400 Series) |
| Temp. range | Max. 75 °C |
| Reduction ratio | Max. 10:1 (200 Series), Max. 20:1 (300 Series), Max. 6:1 (400 Series) |
| Sealant | NBR |
| Spring bonnet | Pressed brass up to DN 25, Grey cast iron from DN 32 |
| Housing | Red brass 2.1096.01 |





Note

Further information on request

Description

Diaphragm pressure regulators with non-self-relieving design and non-pressure-reduced single-seated valve. Very precise adjustment. Good response characteristic because of only a few moving parts which hence minimal friction. Ideal for compressed air, nitrogen and other neutral, non-flammable gases, but only suitable for liquids with comparatively low flow rates.

Ordering information

Other designs available on request

Additional information

Other designs available on request

Item

| Δ | <u></u> | · _ | |
|------|--------------|--------------------------------|--|
| (mm) | В | C (mm) | D (mm) |
| 70,0 | 185.5 mm | 140,0 | 45,5 |
| 70,0 | 185.5 mm | 140,0 | 45,5 |
| 85,0 | 232.5 mm | 186,0 | 46,5 |
| | 70,0 70,0 | 70,0 185.5 mm 70,0 185.5 mm | 70,0 185.5 mm 140,0 70,0 185.5 mm 140,0 |

| Spare parts | |
|------------------|----------------------|
| K-VERSCHLEI-SATZ | Set of wearing parts |