



# K-VLST K AG-K IG MS NI

Extensions, short, conical male thread, parallel female thread -  
nickel-plated brass

**HANSA*****FLEX***

## Properties

Operating temperature	Max. 150 °C
Pressure	Max. 60 bar
Material	Nickel-plated brass



## Note

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.  
Further information on request

## Description

Suitable for air, water, oil, steam, etc.

## Additional information

Further types and dimensions on request.

## Item

Identification	Male thread	Female thread	L1 (mm)	L2 (mm)	AF
K-07 40 38 91	R 1/8	G 1/8	20,0	8,0	14 mm
K-07 40 38 92	R 1/8	G 1/4	22,5	8,0	17 mm
K-07 40 38 98	R 1/8	G 3/8	22,5	8,0	22 mm
K-07 40 38 93	R 1/4	G 1/4	25,0	11,0	17 mm
K-07 40 38 94	R 1/4	G 3/8	28,5	11,0	22 mm
K-07 40 38 95	R 1/4	G 1/2	29,0	11,0	24 mm
K-07 40 38 96	R 3/8	G 3/8	28,5	11,5	22 mm
K-07 40 38 97	R 3/8	G 1/2	32,0	11,5	24 mm
K-07 40 38 99	R 1/2	G 1/2	34,0	14,0	24 mm
K-07 40 39 00	R 1/2	G 3/4	35,0	14,0	32 mm