

# K-ENDLAGEN-RUECKME KUNST M

End position feedback - plastic microswitch

## Properties

<b>Cable gland</b>	M 20 x 1.5
<b>min. switching power</b>	1 mA at 4 V DC
<b>Nominal switching capacity</b>	1 mA to 5 A at 250 V AC
<b>Switching function</b>	Changeover, silver-plated contacts
<b>Protection IP</b>	IP 67, acc. to DIN EN 60529
<b>Temp. range</b>	-20 °C to +70 °C
<b>Housing</b>	Polyamide blue or black
<b>Screw</b>	Stainless steel 1.4301
<b>Shaft</b>	Polyamide PA6, black
<b>Cover</b>	Polycarbonate, transparent
<b>Mounting bridge</b>	PA6 with 30 % glass fibre
<b>Seals</b>	EPDM and NBR
<b>Sealant</b>	NBR



## Note

Further information on request

## Description

Robust type in a plastic housing, Universal indicator for NAMUR sizes 80 x 30 and 130 x 30, Height-adjustable feet that adapt to different pinion projections, ON / OFF position indicator also visible from a distance, Easy-to-adjust, self-locking trip cam

## Item

Identification	Designation
K- 07 30 29 05	End position feedback, M 2 type with microswitch