# K-SAUGKOERBE FUER RUECKSCHLAGV

Strainers for check valves

HANSA FLEX

## Properties

| | |
|---|---|
| **Thread description** | Stainless steel 1.4301 |
| **Temp. range** | max. +150 °C |
| **Sealant** | NBR |
| **Housing, filter fabric** | Stainless steel 1.4301 |






## Description

Corrosion resistant screw-in strainer, all stainless steel, to suit foot-operated or check valves.

## Item

| Identification | Thread | D (mm) | L (mm) | Mesh size (mm) |
|---|---|---|---|---|
| **K- 07 30 30 52** | G 3/8 | 19,0 | 55,0 | 1,0 |
| **K- 07 30 30 47** | G 1/2 | 22,0 | 55,0 | 1,0 |
| **K- 07 30 30 51** | G 3/4 | 29,0 | 62,0 | 1,0 |
| **K- 07 30 30 44** | G 1 | 36,0 | 71,0 | 1,0 |
| **K- 07 30 30 46** | G 1 1/4 | 43,0 | 80,0 | 1,0 |
| **K- 07 30 30 45** | G 1 1/2 | 49,0 | 90,0 | 1,0 |
| **K- 07 30 30 48** | G 2 | 60,0 | 101,0 | 1,0 |
| **K- 07 30 30 49** | G 2 1/2 | 80,0 | 111,0 | 1,8 |
| **K- 07 30 30 50** | G 3 | 92,0 | 125,0 | 1,8 |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*