

# K-3/2 ANFAV 24 V DC HW G

Start-up valves, power supply 24 V DC, with »HW« mounting bracket and silencer

**HANSA FLEX**

## Properties

<b>Input pressure</b>	2.5 - 9 bar
<b>Media temperature</b>	max. 70 °C
<b>Ambient temperature</b>	Max. 70 °C
<b>Electrical connection</b>	Coupler plug PG 9 - form B
<b>Sealant</b>	NBR
<b>Housing</b>	Die-cast aluminium
<b>Flow rate measurement</b>	At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p$ = 1 bar
<b>More information</b>	User manual on request



## Item

Identification	Thread	Flow rate (L/min)	A (mm)	B	C (mm)	D (mm)	Size
K- 07 25 12 05	G 1/4	1600	65,0	131.0 mm	97,0	34,0	300
K- 07 25 12 07	G 3/8	2500	65,0	131.0 mm	97,0	34,0	300
K- 07 25 12 09	G 1/2	2500	65,0	131.0 mm	97,0	34,0	300
K- 07 25 12 11	G 3/8	4500	78,0	142.5 mm	102,0	40,5	400
K- 07 25 12 13	G 1/2	4500	78,0	142.5 mm	102,0	40,5	400

## Accessories

<b>K-VERBINDUNGSELEMENTE</b>	Connecting sets
<b>K-WANDHALTER</b>	Wall bracket
<b>K-HALTERBAUSATZ</b>	Holder