
K-3/2 ANFAV 24 V DC HW G

Start-up valves, power supply 24 V DC, with »HW« mounting bracket and silencer



В

Properties				
Input pressure	2.5 - 9 bar			
Media temperature	max. 70 °C			
Ambient temperature	Max. 70 °C			
Electrical connection	Coupler plug PG 9 - form B			
Sealant	NBR			
Housing	Die-cast aluminium			
Flow rate measurement	At P1 = 8 bar, P2 = 6 bar and pressure drop Δp = 1 bar			
More information	User manual on request			



Item									
Identification	Thread	Flow rate (L/min)	A (mm)	В	C (mm)	D (mm)	Size		
K- 07 25 12 05	G 1/4	1600	65,0	131.0 mm	97,0	34,0	300		
K- 07 25 12 07	G 3/8	2500	65,0	131.0 mm	97,0	34,0	300		
K- 07 25 12 09	G 1/2	2500	65,0	131.0 mm	97,0	34,0	300		
K- 07 25 12 11	G 3/8	4500	78,0	142.5 mm	102,0	40,5	400		
K- 07 25 12 13	G 1/2	4500	78,0	142.5 mm	102,0	40,5	400		

Accessories	
K-VERBINDUNGELEMENTE	Connecting sets
K-WANDHALTER	Wall bracket
K-HALTERBAUSATZ	Holder