## K-LKM S NW10 IG

Safety couplings DN 10, Innengewinde



Properties	
Operating pressure	Max. 16 bar
Flow rate air	4.000 l/min (at 6 bar and Δp = 0.5 bar)
Media temperature	-20 °C to +100 °C
Material	Galvanised steel / brass
Spring	Stainless-steel
Sealant	NBR



## Note

Further information on request

## **Description**

High-quality, robust and durable, one-hand quick disconnect safety couplings, with very high flow rate and only a small pressure drop. The coupling is released fully automatically in two steps. Air is relieved from the coupling before it is completely disconnected, to minimise the risk of injury to the operator from hose ends flying around. The plug is only disconnected from the coupling if the residual pressure has dropped below 0.3 bar. The dreaded "whiplash effect" is thus avoided and the risk of injury virtually eliminated. This safety version conforms to ISO-Standard DIN EN ISO 4414. Suitable for all applications with an above-average air consumption and characterised by extreme conditions.

Item				
Identification	Connection	Length (mm)	AF (mm)	
K- 07 35 13 07	G 3/8 female	62,3	24	
K- 07 35 13 00	G 1/2 female	67,3	25	
K- 07 35 13 05	G 3/4 female	64,5	32	

Additional elements	
K-NIPPEL KUPPL NW10 AG ROBU	Plugs for couplings DN 10, hardened, galvanised steel, robust type, male
K-NIPPEL KUPPL NW10 IG ROBU	Plugs for couplings DN 10, hardened, galvanised steel, robust type, female
K-TUE 1 ST K VZ	Stems for couplings DN 10, hardened, galvanised steel, robust type

28.11.2025 HANSA-FLEX AG www.hansa-flex.com