
K-DRV GEW V RAENDEL

Unidirectional flow control valves, incoming air restriction (»V«), screw connection



Properties				
Operating pressure	Max. 10 bar			
Temp. range	0 °C to +70 °C			
Hollow screw, pivot arm, regulating screw	Nickel-plated brass			
Internal parts	Brass with a bare metal surface			
lip seal O-ring	NBR			
Seals (non-detachable)	Polyamide (glass fibre-reinforced)			





Note

Further information on request

Description

For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

Item						
Identification	Connection	C (mm)	Thread	AF	B (mm)	
K- 07 15 25 19	M 5 female thread	11,5	M 5	8 mm	38,9	
K- 07 15 05 17	G 1/8 female thread	16,0	G 1/8	14 mm	42,4	
K- 07 15 05 13	G 1/4 female thread	22,0	G 1/4	17 mm	51,0	
K- 07 15 25 20	G 3/8 female thread	26,0	G 3/8	20 mm	63,0	