K-ENDVERTEILERDOSEN

End porting box without through-hole thread, PN 15

Properties

Operating pressure	Max. 15 bar
torque mounting hole	4 Nm
torque brass thread	12 Nm
Temp. range	-10 °C to +50 °C
Housing	Glass fibre-reinforced plastic
Thread	Brass



Note

Further information on request

Description

1, 2 or 3-way porting boxes made of high-strength glass fibre-reinforced plastic for a wide range of applications. Available with up to 3 couplings and 2 inlet thread sizes. Optional through-hole thread at the bottom to facilitate the passage of the medium. All porting boxes have a robust, brass threaded insert for high tightening torques, TÜV certified. Suitable for almost any pneumatic application.

Item

Identification	Thread inlet	Connecting thread
K- 07 40 48 12	G 1/2"	1 x G 1/2
K- 07 40 48 13	G 1/2"	2 x G 1/2
K- 07 40 48 14	G 1/2"	3 x G 1/2
K- 07 40 48 15	G 3/4"	1 x G 1/2
K- 07 40 48 16	G 3/4"	2 x G 1/2
K- 07 40 48 17	G 3/4"	3 x G 1/2

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.