
K-LKM S NW10 AG

Safety couplings DN 10, Außengewinde

Properties

Operating pressure	Max. 16 bar
Flow rate air	4.000 l/min (at 6 bar and Δp = 0.5 bar)
Media temperature	-20 °C to +100 °C
Material	Galvanised steel / brass
Spring	Stainless-steel
Sealant	NBR



Note

Further information on request

Description

High-quality, robust and durable, one-hand quick disconnect safety couplings, with very high flow rate and only a small pressure drop. The coupling is released fully automatically in two steps. Air is relieved from the coupling before it is completely disconnected, to minimise the risk of injury to the operator from hose ends flying around. The plug is only disconnected from the coupling if the residual pressure has dropped below 0.3 bar. The dreaded "whiplash effect" is thus avoided and the risk of injury virtually eliminated. This safety version conforms to ISO-Standard DIN EN ISO 4414. Suitable for all applications with an above-average air consumption and characterised by extreme conditions.

Item

Identification	Connection	Length (mm)	AF (mm)
K- 07 35 13 06	R 3/8 male	68,0	24
K- 07 35 12 99	R 1/2 male	70,3	24
K- 07 35 13 04	R 3/4 male	60,8	27

Additional elements

K-NIPPEL KUPPL NW10 AG ROBU	Plugs for couplings DN 10, hardened, galvanised steel, robust type, male
K-NIPPEL KUPPL NW10 IG ROBU	Plugs for couplings DN 10, hardened, galvanised steel, robust type, female
K-TUE 1 ST K VZ	Stems for couplings DN 10, hardened, galvanised steel, robust type

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.