

## Properties

<b>Ambient temperature</b>	-20 °C to +80 °C
<b>Electrical connection</b>	Round plug connector M 12 x 1, 4-pol.
<b>Output signal</b>	2 switching outputs
<b>Accuracy</b>	1% of span
<b>Power supply</b>	DC 15 - 35V
<b>Wetted parts</b>	CrNi steel
<b>Messstofftemperatur</b>	-20 °C to +85 °C
<b>Prozessanschluss</b>	G 1/4
<b>Protection IP</b>	IP 65 and IP 67 (M 12 x 1)
<b>Housing</b>	CrNi steel



## Note

Further information on request

## Description

Electronic pressure switch with digital display, made of stainless steel, for monitoring and measuring pressures in liquids, gases or compressed air. Applications: Machine tools, compressors and pumps, hydraulic and pneumatic systems, machinery in general

Item		
Identification	Connection	Measuring range
K- 07 30 30 07	G 1/4	0 - 1.0 bar
K- 07 30 30 12	G 1/4	0 - 2.5 bar
K- 07 30 30 15	G 1/4	0 - 4.0 bar
K- 07 30 30 18	G 1/4	0 - 6.0 bar
K- 07 30 30 08	G 1/4	0 - 10.0 bar
K- 07 30 30 10	G 1/4	0 - 16.0 bar
K- 07 30 30 13	G 1/4	0 - 25.0 bar
K- 07 30 30 16	G 1/4	0 - 40.0 bar
K- 07 30 30 19	G 1/4	0 - 60.0 bar
K- 07 30 30 09	G 1/4	0 - 100.0 bar
K- 07 30 30 11	G 1/4	0 - 160.0 bar
K- 07 30 30 14	G 1/4	0 - 250.0 bar
K- 07 30 30 17	G 1/4	0 - 400.0 bar
K- 07 30 30 20	G 1/4	0 - 600.0 bar

## Accessories

**K-ELEKTRO DRUCHSCHALTER EDS** Electronic pressure switch EDS