

Properties

Ambient temperature	-20 °C to +80 °C
Electrical connection	Round plug connector M 12 x 1, 4-pol.
Output signal	2 switching outputs
Accuracy	1% of span
Power supply	DC 15 - 35V
Wetted parts	CrNi steel
Messstofftemperatur	-20 °C to +85 °C
Prozessanschluss	G 1/4
Protection IP	IP 65 and IP 67 (M 12 x 1)
Housing	CrNi steel



Note

Further information on request

Description

Electronic pressure switch with digital display, made of stainless steel, for monitoring and measuring pressures in liquids, gases or compressed air. Applications: Machine tools, compressors and pumps, hydraulic and pneumatic systems, machinery in general

Item		
Identification	Connection	Measuring range
K- 07 30 30 07	G 1/4	0 - 1.0 bar
K- 07 30 30 12	G 1/4	0 - 2.5 bar
K- 07 30 30 15	G 1/4	0 - 4.0 bar
K- 07 30 30 18	G 1/4	0 - 6.0 bar
K- 07 30 30 08	G 1/4	0 - 10.0 bar
K- 07 30 30 10	G 1/4	0 - 16.0 bar
K- 07 30 30 13	G 1/4	0 - 25.0 bar
K- 07 30 30 16	G 1/4	0 - 40.0 bar
K- 07 30 30 19	G 1/4	0 - 60.0 bar
K- 07 30 30 09	G 1/4	0 - 100.0 bar
K- 07 30 30 11	G 1/4	0 - 160.0 bar
K- 07 30 30 14	G 1/4	0 - 250.0 bar
K- 07 30 30 17	G 1/4	0 - 400.0 bar
K- 07 30 30 20	G 1/4	0 - 600.0 bar

Accessories

K-ELEKTRO DRUCHSCHALTER EDS Electronic pressure switch EDS