
# K-SCHUTZROHRE EINSCHRAUB

Screw-in thermowells

HANSA FLEX

## Properties

| | |
|---|---|
| **Operating pressure** | Max. 6 bar (copper alloy), Max. 25 bar (stainless steel) |
| **Ø bead** | 26 mm |
| **Ø protective tube** | 10 mm |
| **Material** | Copper alloy, CrNi-Steel 1.4571 |



## Note

Further information on request

## Description

For bimetallic thermometers in the »High quality« series.

## Item

| Identification | Connecting thread | Overall length | AF (mm) | Material |
|---|---|---|---|---|
| **K- 07 20 11 35** | G 1/2 | L1 = 63 mm | 27 | Copper alloy |
| **K- 07 20 11 36** | G 1/2 | L1 = 100 mm | 27 | Copper alloy |
| **K- 07 20 11 37** | G 1/2 | L1 = 160 mm | 27 | Copper alloy |
| **K- 07 20 11 38** | G 1/2 | L1 = 63 mm | 27 | CrNi steel 1.4571 |
| **K- 07 20 11 39** | G 1/2 | L1 = 100 mm | 27 | CrNi steel 1.4571 |
| **K- 07 20 11 40** | G 1/2 | L1 = 160 mm | 27 | CrNi steel 1.4571 |

## Accessories

| | |
|---|---|
| **K-BIMETALLTHERMOMETER 52-2** | Bimetallic thermometers |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*