

# K-DRS WECHSELKONTAK ANFLANSCHBAR DS

Pressure switches, changeover type, suitable for flange mounting  
K-07302861

**HANSA FLEX**

## Properties

|                              |                                                 |
|------------------------------|-------------------------------------------------|
| <b>Design</b>                | Spring-loaded diaphragm (NBR)                   |
| <b>Application</b>           | Air, neutral gases (lubricated or unlubricated) |
| <b>Ambient temperature</b>   | -10 °C to +60 °C                                |
| <b>Electrical connection</b> | Pg 11P coupling plug, acc. to ISO 4400          |
| <b>Switching frequency</b>   | 60/min.                                         |
| <b>Switching voltage</b>     | max. 250 V AC/DC                                |
| <b>Operating principle</b>   | Changeover                                      |
| <b>Protection IP</b>         | IP 65                                           |
| <b>Material</b>              | Plastic Grivory (PA 61/XT)                      |



## Note

Further information on request

## Description

Special pressure switches for pneumatic applications. Extremely precise thanks to the large control diaphragm. Two through holes in the housing for flanging the switch.

## Item

| Identification | Adjustment range |
|----------------|------------------|
| K- 07 30 28 61 | 0,5 - 10,0 bar   |

## Accessory for following products

|                      |                           |
|----------------------|---------------------------|
| K-VT SCHMAL MULTIFIX | Manifolds - narrow design |
| K-VT BREIT MULTIFIX  | Manifolds - wide design   |

## Spare part for following products

|                   |           |
|-------------------|-----------|
| K-VERTEILER HANSA | Manifolds |
|-------------------|-----------|