# K-DRS WECHSELKONTAK ANFLANSCHBAR DS

Pressure switches, changeover type, suitable for flange mounting
K-07302861

## Properties

| | |
|---|---|
| **Design** | Spring-loaded diaphragm (NBR) |
| **Application** | Air, neutral gases (lubricated or unlubricated) |
| **Ambient temperature** | -10 °C to +60 °C |
| **Electrical connection** | Pg 11P coupling plug, acc. to ISO 4400 |
| **Switching frequency** | 60/min. |
| **Switching voltage** | max. 250 V AC/DC |
| **Operating principle** | Changeover |
| **Protection IP** | IP 65 |
| **Material** | Plastic Grivory (PA 61/XT) |




## Note

Further information on request

## Description

Special pressure switches for pneumatic applications. Extremely precise thanks to the large control diaphragm. Two through holes in the housing for flanging the switch.

## Item

| Identification | Adjustment range |
|---|---|
| **K- 07 30 28 61** | 0,5 - 10,0 bar |

## Accessory for following products

| | |
|---|---|
| **K-VT SCHMAL MULTIFIX** | Manifolds - narrow design |
| **K-VT BREIT MULTIFIX** | Manifolds - wide design |

## Spare part for following products

| | |
|---|---|
| **K-VERTEILER HANSA** | Manifolds |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*