

# K-DRS WECHSELKONTAK ANFLANSCHBAR DS

Pressure switches, changeover type, suitable for flange mounting  
K-07302861

**HANSA FLEX**

## Properties

<b>Design</b>	Spring-loaded diaphragm (NBR)
<b>Application</b>	Air, neutral gases (lubricated or unlubricated)
<b>Ambient temperature</b>	-10 °C to +60 °C
<b>Electrical connection</b>	Pg 11P coupling plug, acc. to ISO 4400
<b>Switching frequency</b>	60/min.
<b>Switching voltage</b>	max. 250 V AC/DC
<b>Operating principle</b>	Changeover
<b>Protection IP</b>	IP 65
<b>Material</b>	Plastic Grivory (PA 61/XT)



## Note

Further information on request

## Description

Special pressure switches for pneumatic applications. Extremely precise thanks to the large control diaphragm. Two through holes in the housing for flanging the switch.

## Item

Identification	Adjustment range
K- 07 30 28 61	0,5 - 10,0 bar

## Accessory for following products

K-VT SCHMAL MULTIFIX	Manifolds - narrow design
K-VT BREIT MULTIFIX	Manifolds - wide design

## Spare part for following products

K-VERTEILER HANSA	Manifolds
-------------------	-----------