

# K-DRV ABLD GEW C SCHLITZ

Unidirectional flow control valves, outgoing air restriction (»C«), screw connection

**HANSA FLEX**

## Properties

|   |                                    |
|---|------------------------------------|
| Operating pressure                        | Max. 10 bar                        |
| Temp. range                               | 0 °C to +70 °C                     |
| Hollow screw, pivot arm, regulating screw | Nickel-plated brass                |
| Internal parts                            | Brass with a bare metal surface    |
| lip seal O-ring                           | NBR                                |
| Seals (non-detachable)                    | Polyamide (glass fibre-reinforced) |



## Note

Further information on request

## Description

For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted.

## Item

| Identification | Connection          | C (mm) | Thread | AF    | B (mm) |
|----------------|---------------------|--------|--------|-------|--------|
| K- 07 15 05 40 | M 5 female thread   | 11,5   | M 5    | 8 mm  | 24,5   |
| K- 07 15 05 45 | G 1/8 female thread | 16,0   | G 1/8  | 14 mm | 32,0   |
| K- 07 15 05 41 | G 1/4 female thread | 22,0   | G 1/4  | 17 mm | 40,0   |
| K- 07 15 25 24 | G 3/8 female thread | 26,0   | G 3/8  | 20 mm | 50,0   |
| K- 07 15 25 23 | G 1/2 female thread | 32,0   | G 1/2  | 26 mm | 61,0   |