

K-MV G (NC) V 24 V DC 1 VA

Normally closed, (NC), pilot-operated, 24 V DC VA stainless steel

HANSA FLEX

Properties

| | |
|------------------------------|---|
| Electrical connection | device socket type A in acc. with ISO 4400 for all valves with threads G 3/8 & G 1/2, except valves type 3 & 4. Device socket |
| Thread description | G thread acc. DIN EN ISO 228-1 |
| Media temperature | max. 80 °C when using water or oils; max. 90 °C when using with air |
| Protection IP | IP 65 |
| Max. working pressure | 10 bar |
| Sealant | FPM |
| Housing, valve seat | Stainless steel 1.4301 |
| Internal parts | Stainless steel |



Note

Further information on request

Description

Standard series in two different versions: Directly operated, Pilot-operated

| Item | min. working pressure (bar) | Thread | DN | A (mm) | B (mm) | C (mm) | Type |
|----------------|-----------------------------|--------|------|--------|--------|--------|------|
| K- 07 30 01 28 | 0,50 | G 1/2 | 15,0 | 70,0 | 70,0 | 107,0 | 3 |
| K- 07 30 01 29 | 0,50 | G 3/4 | 20,0 | 70,0 | 82,0 | 115,4 | 3 |
| K- 07 30 01 30 | 0,50 | G 1 | 25,0 | 70,0 | 92,0 | 124,0 | 3 |