

# K-3/2 ANFAV 24 V DC HW G-MINI

Start-up valves, power supply 24 V DC, with »HW« mounting bracket and silencer

**HANSA FLEX**

## Properties

|                       |  |
|-----------------------|--|
| Input pressure        | 2.5 - 9 bar  |
| Media temperature     | max. 70 °C   |
| Ambient temperature   | Max. 70 °C   |
| Electrical connection | Coupler plug PG 9 - form B                                     |
| Sealant               | NBR  |
| Housing               | Die-cast aluminium   |
| Flow rate measurement | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p$ = 1 bar |
| More information      | User manual on request   |



## Item

| Identification | Thread | Flow rate (L/min) | A (mm) | B        | C (mm) | D (mm) | Size |
|----------------|--------|-------------------|--------|----------|--------|--------|------|
| K- 07 25 12 26 | G 1/8  | 550               | 59,0   | 123.5 mm | 93,5   | 30,0   | 200  |
| K- 07 25 12 28 | G 1/4  | 550               | 59,0   | 123.5 mm | 93,5   | 30,0   | 200  |

## Accessories

|                 |              |
|-----------------|--------------|
| K-WANDHALTER    | Wall bracket |
| K-HALTERBAUSATZ | Holder       |

## Accessory for following products

|                   |           |
|-------------------|-----------|
| K-VT 2 ABGAENGE G | Manifolds |
|-------------------|-----------|