K-BOGEN IG AG 45°

Bends 40, 45°, female/male

Properties

Surface	Hot dip galvanised
Temp. range	-20 °C to +300 °C (at 20 bar)
Connecting thread	acc. ISO 7-1
Material	Black malleable iron B350-10, design symbol A
Approval	DIN DVGW



Note

Further information on request

Description

Acc. to DIN EN 10242 (formerly DIN 2950). The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. The fittings are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications.

Additional information

Further types and dimensions on request.

Item

Identification	Thread
K- 07 40 36 46	Rp/R 1/4
K- 07 40 36 49	Rp/R 3/8
K- 07 40 36 45	Rp/R 1/2
K- 07 40 36 48	Rp/R 3/4
K- 07 40 36 42	Rp/R 1
K- 07 40 36 44	Rp/R 1 1/4
K- 07 40 36 43	Rp/R 1 1/2
K- 07 40 36 47	Rp/R 2
K- 07 40 51 28	Rp/R 2 1/2
K- 07 40 51 29	Rp/R 3

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.