

# K-WV 3/2 5/2 NAMUR LB

3/2 and 5/2-way spool valves with NAMUR style interface

**HANSA FLEX**

## Properties

|                              |                               |
|------------------------------|-------------------------------|
| <b>Media</b>                 | Air, neutral gases (filtered) |
| <b>Working pressure</b>      | 1.5 - 8 bar                   |
| <b>Operating temperature</b> | +5 °C to +50 °C               |
| <b>Electrical connection</b> | Plug connector PG 9           |
| <b>Housing</b>               | Aluminium                     |
| <b>Sealant</b>               | NBR                           |



## Note

Further information on request

## Description

Pilot-operated 3/2 and 5/2-way spool valves with threaded ports and a NAMUR style interface. Combines high-quality design with a low price. By adding the conversion plate supplied with each valve, the device can be adapted to a 3/2-way function. The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure. Includes a manual operator as standard.

## Item

| Identification | Voltage      | Port 1 | Port 3 - 5 | DN | Flow rate (L/min) |
|----------------|--------------|--------|------------|----|-------------------|
| K- 07 15 00 09 | 230 V, 50 Hz | G 1/4  | G 1/4      | 8  | 1370              |
| K- 07 15 00 10 | 24 V DC      | G 1/4  | G 1/4      | 8  | 1370              |
| K- 07 15 00 11 | 230 V, 50 Hz | G 3/8  | G 1/4      | 10 | 1650              |
| K- 07 15 00 12 | 24 V DC      | G 3/8  | G 1/4      | 10 | 1650              |