


K-W90 AG-K ISO 7-1 VA

Male elbows, conical male thread acc. to ISO 7-1, stainless steel

HANSA FLEX

Properties

Pressure range	Max. 25 bar
Recommended hoses	PTFE hose
Temp. range	-40 °C to +200 °C (depending on the hose quality and diameter)
Material	Stainless steel 1.4404
Seal	Pure metal



Note

Further information on request

Description

Supplied without seals. For use with corrosive media and at high temperatures. Screw fitting series made of stainless steel for all applications where compliance with strict tightness, pressure and temperature requirements is essential. The parts are manufactured without rubber seals, in other words they are ideal for very high temperatures or for use with corrosive liquids, e.g. in cases when FPM is no longer suitable.

Item

Identification	Thread	for hose	L1 (mm)	L2 (mm)	AF1 (mm)	AF2 (mm)
K- 07 40 30 32	R 1/8	6 mm / 4 mm	23,0	17,0	12	10
K- 07 40 30 33	R 1/8	8 mm / 6 mm	23,0	17,0	14	10
K- 07 40 30 30	R 1/4	6 mm / 4 mm	23,0	21,5	12	10
K- 07 40 30 31	R 1/4	8 mm / 6 mm	23,0	21,5	14	10
K- 07 40 30 29	R 1/4	10 mm / 8 mm	26,0	21,5	16	12