
## K-L-AGR-K OR DRH VA

Male run tees, conical male thread acc. to ISO 7-1, stainless steel



Properties	
Pressure range	Max. 25 bar
Recommended hoses	PTFE hose
Temp. range	-40 °C to +200 °C (depending on the hose quality and diameter)
Material	Stainless steel 1.4404
Seal	Pure metal





## Note

Further information on request

## **Description**

Supplied without seals. For use with corrosive media and at high temperatures. Screw fitting series made of stainless steel for all applications where compliance with strict tightness, pressure and temperature requirements is essential. The parts are manufactured without rubber seals, in other words they are ideal for very high temperatures or for use with corrosive liquids, e.g. in cases when FPM is no longer suitable.

Item								
Identification	Thread	for hose	L1 (mm)	L2 (mm)	AF1 (mm)	AF2 (mm)		
K- 07 40 30 51	R 1/8	6 mm / 4 mm	23,0	40,0	12	10		
K- 07 40 30 52	R 1/8	8 mm / 6 mm	23,0	40,0	14	10		
K- 07 40 30 49	R 1/4	6 mm / 4 mm	23,0	44,5	12	10		
K- 07 40 30 50	R 1/4	8 mm / 6 mm	23,0	44,5	14	10		
K- 07 40 30 48	R 1/4	10 mm / 8 mm	26,0	47,5	16	12		