

# K-SCHLAUCHTUELLEN KUPP

Hose stems for couplings DN 7.2 - DN 7.8, swivel type, nickel-plated brass / steel, male

**HANSA FLEX**

## Properties

<b>Operating pressure</b>	0 - 35 bar, maximum static working pressure (non-pulsating)
<b>Flow rate air</b>	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
<b>Media temperature</b>	0 °C to +70 °C
<b>Housing, sleeve, valve body</b>	Nickel-plated brass
<b>Spring, snap ring, balls</b>	Stainless steel
<b>Sealant</b>	NBR



## Note

Further information on request

## Item

Identification	Connection	LW (mm)	Material
K- 07 35 02 02	G 1/4 male	6	Nickel-plated brass
K- 07 35 02 03	G 1/4 male	8	Nickel-plated brass
K- 07 35 02 04	G 1/4 male	9	Nickel-plated brass
K- 07 35 02 05	G 1/4 male	10	Nickel-plated brass
K- 07 35 01 78	G 1/4 male	13	Nickel-plated brass
K- 07 35 02 15	R 3/8 male	6	Nickel-plated steel
K- 07 35 02 16	R 3/8 male	9	Nickel-plated steel