


# K-TUE IG MS NI

Female stems with parallel female thread - nickel-plated brass

**HANSA FLEX**

## Properties

Operating temperature	Max. 150 °C
Pressure	Max. 60 bar
Material	Nickel-plated brass



## Note

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. Further information on request

## Description

Suitable for air, water, oil, steam, etc.

## Additional information

Further types and dimensions on request.

Item	Identification	Thread	for hose	L1 (mm)	L2 (mm)	AF
	K- 07 40 11 76	G 1/8	LW 6 mm	28,0	8,5	12 mm
	K- 07 40 11 77	G 1/8	LW 8 mm	28,0	8,5	12 mm
	K- 07 40 11 78	G 1/8	LW 9 mm	28,0	8,5	12 mm
	K- 07 40 11 79	G 1/8	LW 10 mm	28,0	8,5	12 mm
	K- 07 40 11 80	G 1/4	LW 6 mm	33,0	10,0	15 mm
	K- 07 40 11 81	G 1/4	LW 8 mm	33,0	10,0	15 mm
	K- 07 40 11 82	G 1/4	LW 9 mm	33,0	10,0	15 mm
	K- 07 40 11 83	G 1/4	LW 10 mm	33,0	10,0	15 mm
	K- 07 40 11 84	G 1/4	LW 12 mm	33,0	10,0	15 mm
	K- 07 40 11 85	G 3/8	LW 8 mm	35,0	12,0	19 mm
	K- 07 40 11 86	G 3/8	LW 10 mm	35,0	12,0	19 mm
	K- 07 40 11 87	G 3/8	LW 12 mm	35,0	12,0	19 mm
	K- 07 40 11 88	G 3/8	LW 14 mm	35,0	12,0	19 mm
	K- 07 40 11 89	G 1/2	LW 10 mm	38,0	14,0	25 mm
	K- 07 40 11 90	G 1/2	LW 12 mm	41,0	14,0	25 mm
	K- 07 40 11 91	G 1/2	LW 14 mm	41,0	14,0	25 mm