

# K-DROSSELPLATT NAMUR VENTIL

Flow regulators for NAMUR valves

**HANSA FLEX**

## Properties

<b>Media</b>	Air, neutral gases, filtered
<b>Working pressure</b>	0.5 to 10 bar
<b>Operating temperature</b>	-20 °C to +70 °C
<b>content of delivery</b>	1 coding pin (not for K-07152240), 2 O-rings, 2 fixing screws
<b>Housing</b>	Aluminium, anodised
<b>Material</b>	Gasket: NBR
<b>Sealant</b>	NBR



## Note

Further information on request

## Description

Block-form flow regulator as an intermediate plate between the control valve and actuator acc. to the G 1/4 NAMUR standard. 3/2-way flow regulators: Independent regulation of the forward and return strokes of a single-acting pneumatic actuator. 5/2-way flow regulators: Regulation of the forward and return strokes of a double-acting pneumatic actuator.

## Item

Identification	Function	Operation	DN	Flow rate (L/min)
K- 07 15 22 39	3/2-way	Knurled Screw	5	650
K- 07 15 22 40	3/2-way	Screwdriver	5	650
K- 07 15 22 41	5/2-way	Knurled Screw	5	650
K- 07 15 22 42	5/2-way	Screwdriver	5	650