

# K-ZWEIHAND S VENTILE O GEH

Two-hand safety valve without housing

## Properties

|                                      |                                       |
|--------------------------------------|---------------------------------------|
| <b>Media</b>                         | Filtered, unlubricated compressed air |
| <b>Operating pressure</b>            | 2.5 - 8 bar                           |
| <b>Temp. range</b>                   | -10 °C to +60 °C                      |
| <b>Connection</b>                    | Push-in fitting for pipe 4 mm         |
| <b>Operation</b>                     | Pneumatic                             |
| <b>Flow rate air 6bar</b>            | 85 NI/min                             |
| <b>max. time-offset input signal</b> | 0,4 s                                 |



## Note

Further information on request

## Description

This pushbutton panel according to EN574 Type III A is comprised of a dual manual control valve with a housing and manifold. The valve only generates an output signal if two synchronised input signals are received within < 0.4 sec. If one input signal is interrupted, the output signal is interrupted as well. An emergency stop valve with a mushroom pushbutton is included. The housing can be screwed to the wall in any position. The valve manifold can optionally be supplied without the housing and with a DIN bar adapter. Applications: Two-hand safety valve for start-of-cycle control on a pneumatically operated machine.

## Item

| Identification | Designation                           | Connection                    |
|----------------|---------------------------------------|-------------------------------|
| K- 07 15 26 09 | Two-hand safety valve without housing | Push-in fitting for 4 mm pipe |
| K- 07 15 26 10 | mounting element                      | -                             |