

# K-BKR GELB STAHLHEBEL IG IG

Ball valves with yellow steel lever, lightweight type, female/female thread

**HANSA FLEX**

## Properties

|                              |  |
|------------------------------|--|
| <b>Application</b>           | Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture |
| <b>Operating pressure</b>    | Max. 40 bar  |
| <b>Operating temperature</b> | -15 °C to +90 °C   |
| <b>Thread description</b>    | G thread acc. DIN EN ISO 228-1   |
| <b>Housing</b>               | Nickel-plated brass  |
| <b>Lever</b>                 | Steel, with plastic coating  |
| <b>Ball</b>                  | Chrome-plated brass  |
| <b>Ball seals</b>            | PTFE   |
| <b>Stem seal</b>             | HNBR / EPDM / PTFE. 2 O-Rings (HNBR / EPDM) 1 gasket (PTFE)<br>additional PTFE-gasket  |



## Note

Further information on request

## Item

| Identification | DN | Thread  | A (mm) | B (mm) | L (mm) |
|----------------|----|---------|--------|--------|--------|
| K- 07 30 00 81 | 8  | G 1/4   | 85,0   | 42,0   | 39,0   |
| K- 07 30 00 85 | 10 | G 3/8   | 85,0   | 42,0   | 43,0   |
| K- 07 30 00 89 | 15 | G 1/2   | 85,0   | 46,0   | 50,0   |
| K- 07 30 00 93 | 20 | G 3/4   | 105,0  | 53,0   | 58,0   |
| K- 07 30 00 97 | 25 | G 1     | 105,0  | 57,0   | 69,0   |
| K- 07 30 01 01 | 32 | G 1 1/4 | 130,0  | 70,0   | 81,0   |
| K- 07 30 01 05 | 40 | G 1 1/2 | 130,0  | 76,0   | 93,0   |
| K- 07 30 01 09 | 50 | G 2     | 165,0  | 92,0   | 110,0  |