K-BKR BLAU STAHLHEBEL IG AG


Ball valves with blue steel lever, lighweight type, female/male thread

HANSA-FLEX

Properties

Application	Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture
Operating pressure	Max. 40 bar
Operating temperature	-15 °C to +90 °C
Thread description	G thread acc. DIN EN ISO 228-1
Housing	Nickel-plated brass
Lever	Steel, with plastic coating
Ball	Chrome-plated brass
Ball seals	PTFE
Stem seal	HNBR / EPDM / PTFE. 2 O-Rings (HNBR / EPDM) 1 gasket (PTFE) additional PTFE-gasket





Note

Further information on request

Item

Identification	DN	Thread	A (mm)	B (mm)	L (mm)
K- 07 30 00 48	8	G 1/4	85,0	42,0	44,0
K- 07 30 00 52	10	G 3/8	85,0	42,0	51,0
K- 07 30 00 56	15	G 1/2	85,0	46,0	60,0
K- 07 30 00 60	20	G 3/4	105,0	53,0	70,0
K- 07 30 00 64	25	G 1	105,0	57,0	79,0
K- 07 30 00 68	32	G 1 1/4	130,0	70,0	91,0
K- 07 30 00 72	40	G 1 1/2	130,0	76,0	104,0
K- 07 30 00 76	50	G 2	165,0	92,0	122,0

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.