

# K-DMUF 1

Pressure transmitters (CrNi steel 1.4404)

**HANSA FLEX**

## Properties

|                       |  |
|-----------------------|--|
| Type                  | A-10   |
| Voltage               | 8 - 30 V   |
| Electrical connection | With right-angle connector acc. to DIN EN 175301-803 A |
| Protection IP         | IP 65 acc. to EN 60529                                 |
| Output signal         | 4 to 20 mA, 2-wire                                     |
| Nonlinearity          | 0.5% of span   |
| Media temperature     | 0 °C to +80 °C   |
| Ambient temperature   | 0 °C to +80 °C   |
| Wetted parts          | CrNi steel 1.4404                                      |
| Housing               | CrNi steel 1.4404                                      |



## Note

Further information on request

## Description

Standard type for universal applications. Suitable for electronic pressure measurements in the low and high-pressure ranges.

## Additional information

Further measuring ranges on request

Pressure converter with output signal 0 - 10 V, 0 - 5 V and others on request.

## Item

| Identification | Measuring range | Thread |
|----------------|-----------------|--------|
| K- 07 20 10 46 | 0 - 1.0 bar     | G 1/4  |
| K- 07 20 10 47 | 0 - 1.6 bar     | G 1/4  |
| K- 07 20 10 48 | 0 - 2.5 bar     | G 1/4  |
| K- 07 20 10 49 | 0 - 4.0 bar     | G 1/4  |
| K- 07 20 10 50 | 0 - 6.0 bar     | G 1/4  |
| K- 07 20 10 51 | 0 - 10.0 bar    | G 1/4  |
| K- 07 20 10 52 | 0 - 16.0 bar    | G 1/4  |
| K- 07 20 10 53 | 0 - 25.0 bar    | G 1/4  |
| K- 07 20 10 54 | 0 - 40.0 bar    | G 1/4  |
| K- 07 20 10 55 | 0 - 60.0 bar    | G 1/4  |
| K- 07 20 10 56 | 0 - 100.0 bar   | G 1/4  |
| K- 07 20 10 57 | 0 - 160.0 bar   | G 1/4  |
| K- 07 20 10 58 | 0 - 250.0 bar   | G 1/4  |
| K- 07 20 10 59 | 0 - 400.0 bar   | G 1/4  |
| K- 07 20 10 60 | 0 - 600.0 bar   | G 1/4  |