

K-TUE 7,2 7,8 MS NI

Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass

Properties

Operating pressure	0 - 35 bar, maximum static working pressure (non-pulsating)
Media temperature	-20 °C to +100 °C
Material	Nickel-plated brass



Note

Further information on request

Item

Identification	Designation
K- 07 35 01 76	Stem, I.D. 6
K- 07 35 01 88	Stem, I.D. 8
K- 07 35 01 77	Stem, I.D. 9
K- 07 35 01 89	Stem, I.D. 10
K- 07 35 01 84	Stem, I.D. 13

Additional element for following products

K-SVKM NW 7,8 AG H	Quick disconnect couplings DN 7.8 - for extremely high flow rates, male
K-SVKM NW 7,8 IG H	Quick disconnect couplings DN 7.8 - for extremely high flow rates, female
K-SVKM NW 7,8 SCHL TUE H	Quick disconnect couplings DN 7.8 - for extremely high flow rates, with hose stem
K-LKM S NW7,8 AG	Safety couplings DN 7.8, male
K-LKM S NW7,8 IG	Safety couplings DN 7.8, female
K-LKM S NW7,8 SCHL TUE	Safety couplings DN 7.8, with hose stem