


# K-NIPPEL KUPPL NW7 AG MS NI

Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male

**HANSA FLEX**

## Properties

Operating pressure	0 - 35 bar, maximum static working pressure (non-pulsating)
Media temperature	-20 °C to +100 °C
Material	Nickel-plated brass



## Note

Further information on request

## Item

Identification	Designation	AF (mm)
K- 07 35 01 92	Plug G 1/8 male	14
K- 07 35 01 93	Plug G 1/4 male	17
K- 07 35 01 94	Plug G 3/8 male	19
K- 07 35 01 95	Plug G 1/2 male	24

## Additional element for following products

K-SVKM NW 7,8 AG H	Quick disconnect couplings DN 7.8 - for extremely high flow rates, male
K-SVKM NW 7,8 IG H	Quick disconnect couplings DN 7.8 - for extremely high flow rates, female
K-SVKM NW 7,8 SCHL TUE H	Quick disconnect couplings DN 7.8 - for extremely high flow rates, with hose stem
K-LKM S NW7,8 AG	Safety couplings DN 7.8, male
K-LKM S NW7,8 IG	Safety couplings DN 7.8, female
K-LKM S NW7,8 SCHL TUE	Safety couplings DN 7.8, with hose stem