

# K-SVKM NW 5 AG MS BL

Quick disconnect couplings DN 5, brass with a bare metal surface, male

**HANSA FLEX**

## Properties

|                                    |   |
|------------------------------------|---|
| <b>Operating pressure</b>          | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| <b>Flow rate air</b>               | 560 l/min (at 6 bar and $\Delta p = 0.5$ bar)               |
| <b>Media temperature</b>           | -20 °C to +100 °C   |
| <b>Housing, sleeve, valve body</b> | Brass   |
| <b>Spring, snap ring, balls</b>    | Stainless steel   |
| <b>Sealant</b>                     | NBR   |



## Note

Further information on request

## Description

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. Ideal for: Pneumatic tools, pneumatic applications, medical equipment, instrumentation and control, laboratory, chemical applications, analysis, metering techniques.

## Item

| Identification | Connection | Length (mm) | AF (mm) |
|----------------|------------|-------------|---------|
| K- 07 35 06 34 | G 1/8 male | 37,0        | 14      |
| K- 07 35 06 35 | G 1/4 male | 38,0        | 17      |
| K- 07 35 06 36 | G 3/8 male | 38,0        | 19      |