

# K-SVKM NW 7,2 AG VA

Quick disconnect couplings DN 7.2, stainless steel, male

**HANSA FLEX**

## Properties

<b>Operating pressure</b>	1 - 35 bar and rough vacuum
<b>Flow rate air</b>	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
<b>Media temperature</b>	-25 °C to +200 °C
<b>Housing, sleeve, valve body</b>	Stainless steel 1.4305
<b>Spring, snap ring</b>	Stainless steel 1.4310
<b>Locking pins</b>	Stainless steel 1.4401
<b>Sealant</b>	FKM



## Note

Further information on request

## Description

Classic standard coupling type, one side sealing, made of stainless steel. The closed sleeve protects the coupling from dirt. We recommend the use of stainless steel plugs and stems!

## Item

Identification	Connection	Length (mm)	AF (mm)
K- 07 35 07 59	G 1/4 male	43,0	22
K- 07 35 07 60	G 3/8 male	43,0	22
K- 07 35 07 61	G 1/2 male	46,0	24

## Additional elements

K-NIPPEL KUPPL NW7 AG VA 2	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, male
K-NIPPEL KUPPL NW7 IG VA 1	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, female
K-TUE 7,2 7,8 VA 2	Stems for couplings DN 7.2 - DN 7.8, stainless steel 1.4305