

K-SVKM NW 7,8 AG H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, male

HANSA FLEX

Properties

| | |
|---------------------------------|---------------------------------------|
| Operating pressure | 0 - 35 bar |
| Flow rate air | 2.100 l/min (at $\Delta p = 0.5$ bar) |
| Media temperature | -20 °C to +40 °C |
| Threaded element | Nickel-plated brass |
| Valve body | Steel, QPQ treated |
| Unlocking sleeve | Extremely robust, ergonomic plastic |
| Valve, Seat | Brass |
| Media | Only for clean compressed air |
| Seals | NBR |
| Spring, snap ring, balls | stain less steel |



Note

Further information on request

Description

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

Item

| Identification | Connection | Length (mm) | AF (mm) |
|----------------|------------|----------------|------------|
| K- 07 35 08 47 | G 1/4 male | 65,0 | 19 |
| K- 07 35 08 48 | G 3/8 male | 65,0 | 19 |
| K- 07 35 08 49 | G 1/2 male | 59,0 | 22 |

Additional elements

| | |
|-------------------------------|--------------------------------------------------------------------------------------------------------------|
| K-NIPP KUPPL NW7 SCHL MS NI K | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring |
| K-NIPPEL KUPPL NW7 AG MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male |
| K-NIPPEL KUPPL NW7 IG MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female |
| K-NIPPEL KUPPL NW7 SCHL MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose |
| K-TUE 7,2 7,8 MS NI | Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass |