


K-SVKM NW 7,2 ABSP TUE MS

Quick disconnect couplings DN 7.2, both sides sealing, brass, with hose stem

HANSA FLEX

Properties

| | |
|------------------------------------|---|
| Operating pressure | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Flow rate air | 700 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| Media temperature | -20 °C to +100 °C |
| Housing, sleeve, valve body | Brass |
| Spring, snap ring, balls | Stainless steel |
| Sealant | NBR |



Note

Further information on request

Description

Couplings, stems and plugs are fitted with a valve. Connection: Both valves open and the medium is allowed to pass. Disconnection: Both valves close and the medium is prevented from escaping.

Item

| Identification | Connection | Length (mm) | AF (mm) |
|----------------|---------------|-------------|---------|
| K- 07 35 07 56 | Stem, I.D. 6 | 58,0 | 21 |
| K- 07 35 12 72 | Stem, I.D. 8 | 58,0 | 21 |
| K- 07 35 07 57 | Stem, I.D. 9 | 58,0 | 21 |
| K- 07 35 12 74 | Stem, I.D. 10 | 58,0 | 21 |
| K- 07 35 07 58 | Stem, I.D. 13 | 58,0 | 21 |