
## K-WV 5/2 EINS ELEKTRO

5/2-way spool valves, single solenoid



Duamantias			
Properties			
Operating principle	5/2-way		
Operating pressure	2.5 - 10 bar; Max. vacuum 10 bar (external pilot air)		
min. working pressure	2,5 bar		
Temp. range	-10 °C to +60 °C		
Flow rate 6bar and 10bar	1500 NI/min (G 1/4), 4600 NI/min (G 1/2)		
Electrical connection	Coupler plug PG 9 - form B		
Protection IP	IP 65 (DIN 46244)		
Housing	Anodised aluminium, blue		
Piston gate valve	Stainless steel		
Sealant	NBR		
•	· · · · · · · · · · · · · · · · · · ·		





## Note

Further information on request

## Description

This valve design, featuring the Tapered Tee Seal®, offers the ability to run without lubrication and supports almost any compressed air quality. <br/>
<br/

Item							
Identification	Connection	Voltage	DN	circuit diagram number	Control		
K- 07 15 02 21	G 1/4	24 V DC	8	35			
K- 07 15 02 22	G 1/2"	24 V DC	15	35			
K- 07 15 02 23	G 1/4	230 V AC, 50 Hz	8	35			
K- 07 15 02 24	G 1/2"	230 V AC, 50 Hz	15	35			