

# K-PRAEZIONS STEUERREGLER

Precision pilot regulators (feedback)

**HANSA FLEX**

## Properties

|                                 |                       |
|---------------------------------|-----------------------|
| <b>Input pressure</b>           | Max. 16 bar           |
| <b>Media temperature</b>        | max. 80 °C            |
| <b>Ambient temperature</b>      | Max. 80 °C            |
| <b>Port for pressure gauge</b>  | For feedback pressure |
| <b>Sealant</b>                  | FKM                   |
| <b>Housing</b>                  | Die-cast zinc         |
| <b>Diaphragm</b>                | FKM                   |
| <b>Internal air consumption</b> | 3 to 6 l/min          |



## Note

Further information on request

## Description

Diaphragm pressure regulator for feedback systems, specially designed for use in a pneumatically controlled closed control loop in combination with a pressure regulator with pneumatic remote control, e.g. our Art. Nos. K-07250505 to K-07250510.

## Item

| Identification | Thread | Control range | A<br>(mm) | B        | C<br>(mm) | D<br>(mm) |
|----------------|--------|---------------|-----------|----------|-----------|-----------|
| K- 07 25 05 11 | G 1/4  | 0.2 - 7 bar   | 82,0      | 142.8 mm | 19,4      | 123,4     |

## Accessories

|                                 |        |
|---------------------------------|--------|
| <b>K-HALTERBAUSATZ STANDARD</b> | Holder |
|---------------------------------|--------|