

K-PRAEZI DRUCKREGL OHNE EIGENLUF

Precision pressure regulators without air consumption

HANSA FLEX

Properties

Input pressure	Max. 16 bar
Media temperature	max. 80 °C
Ambient temperature	Max. 80 °C
Media	Fine-filtered (5 µm), unlubricated compressed air, neutral gases
Port for pressure gauge	G 1/4
Sealant	NBR
Housing	Die-cast zinc
Valve cone, diaphragm	FPM



Note

Further information on request

Description

Diaphragm pressure regulators with self-relieving design for applications requiring an accurate working pressure.

Item

Identification	Thread	Control range	Flow rate (L/min)	A (mm)	B	C (mm)	D (mm)
K- 07 25 09 39	G 1/4	0 - 1 bar	600	82,0	148.0 mm	19,5	128,5
K- 07 25 09 40	G 1/4	0.1 - 3 bar	760	82,0	148.0 mm	19,5	128,5
K- 07 25 09 41	G 1/4	0.2 - 6 bar	550	82,0	148.0 mm	19,5	128,5
K- 07 25 09 42	G 1/4	0.5 - 10 bar	400	82,0	148.0 mm	19,5	128,5

Accessories

K-HALTERBAUSATZ STANDARD Holder