

# K-PRAEZI DRUCKREGL OHNE EIGENLUF

Precision pressure regulators without air consumption

**HANSA FLEX**

## Properties

<b>Input pressure</b>	Max. 16 bar
<b>Media temperature</b>	max. 80 °C
<b>Ambient temperature</b>	Max. 80 °C
<b>Media</b>	Fine-filtered (5 µm), unlubricated compressed air, neutral gases
<b>Port for pressure gauge</b>	G 1/4
<b>Sealant</b>	NBR
<b>Housing</b>	Die-cast zinc
<b>Valve cone, diaphragm</b>	FPM



## Note

Further information on request

## Description

Diaphragm pressure regulators with self-relieving design for applications requiring an accurate working pressure.

## Item

Identification	Thread	Control range	Flow rate (L/min)	A (mm)	B	C (mm)	D (mm)
K- 07 25 09 39	G 1/4	0 - 1 bar	600	82,0	148.0 mm	19,5	128,5
K- 07 25 09 40	G 1/4	0.1 - 3 bar	760	82,0	148.0 mm	19,5	128,5
K- 07 25 09 41	G 1/4	0.2 - 6 bar	550	82,0	148.0 mm	19,5	128,5
K- 07 25 09 42	G 1/4	0.5 - 10 bar	400	82,0	148.0 mm	19,5	128,5

## Accessories

K-HALTERBAUSATZ STANDARD Holder