K-ROHRDOPPELNIPPEL MS

Double pipe nipples, brass

HANSA FLEX

Properties

Working pressure	10 bar
Media temperature	max. 90 °C
Ambient temperature	Max. 90 °C
Connecting thread	R-thread to EN 10226
Material	Brass with a bare metal surface



Note

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.
Further information on request

Item

Identification	Thread	Length (mm)
K- 07 40 16 25	G 1/2	30,0
K- 07 40 16 26	G 1/2	40,0
K- 07 40 16 27	G 1/2	50,0
K- 07 40 16 28	G 1/2	60,0
K- 07 40 16 29	G 1/2	80,0
K- 07 40 16 20	G 1/2	100,0
K- 07 40 16 21	G 1/2	120,0
K- 07 40 16 22	G 1/2	150,0
K- 07 40 16 23	G 1/2	180,0
K- 07 40 16 24	G 1/2	200,0
K- 07 40 16 41	G 3/4	40,0
K- 07 40 16 42	G 3/4	60,0
K- 07 40 16 43	G 3/4	80,0
K- 07 40 16 36	G 3/4	100,0
K- 07 40 16 37	G 3/4	120,0
K- 07 40 16 38	G 3/4	150,0
K- 07 40 16 39	G 3/4	180,0
K- 07 40 16 40	G 3/4	200,0
K- 07 40 16 04	G 1	40,0
K- 07 40 16 05	G 1	60,0
K- 07 40 16 06	G 1	80,0
K- 07 40 15 99	G 1	100,0
K- 07 40 16 00	G 1	120,0
K- 07 40 16 01	G 1	150,0
K- 07 40 16 02	G 1	180,0
K- 07 40 16 03	G 1	200,0
K- 07 40 16 18	G 1 1/4	60,0
K- 07 40 16 19	G 1 1/4	80,0
K- 07 40 16 13	G 1 1/4	100,0
K- 07 40 16 14	G 1 1/4	120,0
K- 07 40 16 15	G 1 1/4	150,0
K- 07 40 16 16	G 1 1/4	180,0
K- 07 40 16 17	G 1 1/4	200,0
K- 07 40 16 11	G 1 1/2	60,0
K- 07 40 16 12	G 1 1/2	80,0
K- 07 40 16 07	G 1 1/2	100,0
K- 07 40 16 08	G 1 1/2	120,0
K- 07 40 16 09	G 1 1/2	150,0
K- 07 40 16 10	G 1 1/2	200,0
K- 07 40 16 34	G 2	60,0
K- 07 40 16 35	G 2	80,0
K- 07 40 16 30	G 2	100,0
K- 07 40 16 31	G 2	120,0
K- 07 40 16 32	G 2	150,0
K- 07 40 16 33	G 2	200,0

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.