# K-ENDPLATTEN V

End plate for HDM valve terminal

## Properties

| | |
|---|---|
| **Media** | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| **Working pressure** | Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard) |
| **Pilot pressure** | 3 - 7 bar |
| **Temp. range** | -10 °C to +60 °C |
| **Flow rate** | 200 Nl/min (Ø 4), 500 Nl/min (Ø 6), 800 Nl/min (Ø 8) |
| **No. of pilots** | Max. 16 (e.g. 16 spring return valves) |
| **Operating principle** | Blind (terminates the system) |
| **Manual control** | Latching (bistable), Monostable (non-latching) version also available on request |
| **Power input** | 0.6 W per pilot |
| **Protection IP** | IP 65 |



## Note

Further information on request

## Description

These compact valve terminals, with a maximum flow rate of 800 Nl/min, can be individually adapted to the specific conditions of each application thanks tot he wide range of functions and various input and intermediate plates.Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

## Additional information

Important: The scope of supply does not include a connector. Please order separately.

## Item

| Identification | Function |
|---|---|
| **K- 07 15 22 50** | Blind (terminates the system) |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*