


K-ELEKTRISCHE ANSCHLUESSE

Electrical connection (multi-pole, 25-pin, IP 65)



Properties	
Media	Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Working pressure	Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)
Pilot pressure	3 - 7 bar
Temp. range	-10 °C to +60 °C
Flow rate	200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8)
No. of pilots	Max. 16 (e.g. 16 spring return valves)
Manual control	Latching (bistable), Monostable (non-latching) version also available on request
Power input	0.6 W per pilot
Protection IP	IP 65

Note

Further information on request

Description

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Additional information

Important: The scope of supply does not include a connector. Please order separately.

Item	
Identification	Designation
K- 07 15 22 45	IP 67 connector, 25-pin, with 1 m cable
K- 07 15 22 46	IP 67 connector, 25-pin, with 2.5 m cable
K- 07 15 22 47	IP 67 connector, 25-pin, with 5 m cable