
K-WTEH 2-TLG PC-BEHAEL S W H G-MINI

Service units, 2-piece with polycarbonate bowl and joiner for wall mounting, semi-automatic drain valve



Properties				
Input pressure	Max. 10 bar			
Media temperature	max. 70 °C			
Ambient temperature	Max. 70 °C			
Pore size in filter element	5 μm			
Sealant	NBR			
Spring bonnet	POM			
Housing	Die-cast aluminium			
Dropper	Brass/POM			
Drain valve	Semi-automatic			
Flow rate measurement	At P1 = 8 bar, P2 = 6 bar and pressure drop Δp = 1 bar			
More information	User manual on request			





Item								
Identification	Thread	Control range	Flow rate	Α	В	С	D	Size
			(L/min)	(mm)		(mm)	(mm)	
K- 07 25 14 09	G 1/8	1.5 - 9 bar	500	88,0	161,0 mm	68,0	93,0	200
K- 07 25 14 10	G 1/4	1.5 - 9 bar	500	88,0	161,0 mm	68,0	93,0	200

Accessories				
K-VERSCHLEI-SATZ	Set of wearing parts			
K-ERSATZMEMBRANE	Replacement diaphragm			
K-ADAPTERPLATTEN HANSA	Adapter plate HANSA			
K-FILTERELEMENT	Filter element			
K-VERBINDUNGELEMENTE	Connecting sets			
K-WANDHALTER	Wall bracket			