
K-WTEH SERIE ONE O DRS

Service units, »ONE« Series, without pressure switch



Properties				
Input pressure	Max. 10 bar			
Temp. range	-10 °C to +50 °C			
Media	Compressed air			
Protection IP	IP 65			
Working pressure	0.5 - 8 bar			
Pressure switches	Changeover contact			
Pore size in filter element	20 μm			
Flow rate measurement	At 6,3 bar and Δp = 1 bar			





Note

Further information on request

Description

Multifunctional service unit with 6 or 7 functions in a single device: 3/2-way valve (manually operated), filter with automatic drain valve, air ports, pressure regulator, pressure gauge, soft start valve and optional: pressure switch. This combination of extremely good flow rates and a wide range of functions integrated in a single, compact unit saves valuable space and is unmatched by any similar product available in the market! Soft starting independently of the load and easy replacement of the filter cartridge under pressure are just two of the other outstanding features of this amazing device.

Ordering information

This unit can also be supplied with many other combinations of functions and port sizes. We will be pleased to make you an offer to match your individual specification on request!

Item						
Identification	Connection	Flow rate	A (mm)	В	C (mm)	Voltage
K- 07 25 13 79	G 1/4	2400	165,5	144.0 mm	35,0	24 V DC (for valves and pressure switch)
K- 07 25 13 80	G 3/8	3300	165,5	144.0 mm	35,0	24 V DC (for valves and pressure switch)
K- 07 25 13 81	G 1/2"	4000	165,5	144.0 mm	35,0	24 V DC (for valves and pressure switch)