K-WV 3/2 5/2 NAMUR LB LF

3/2- and 5/2-way spool valves with NAMUR style interface and air spring



Properties					
Media	Air, neutral gases (filtered)				
Working pressure	1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22)				
Operating temperature	-20 °C to +50 °C				
Connection 1 - 3	G 1/4 (Port 1), G 1/4 (Port 3 and 5)				
Port 1/3 + 5	G 1/4 (Port 1), G 1/4 (Port 3 and 5)				
Electrical connection	Plug connector PG 9				
content of delivery	Plug connector PG 9, conversion plate, screws and seal				
Power input	3 W=/5 VA~				
Housing	Anodised aluminium				
Slider	Stainless steel				
Sealant	NBR				



Note

Further information on request

Description

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function.

Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

Item						
Identification	Voltage	Port 1	Port 3 - 5	DN	Flow rate	
K- 07 15 00 13	230 V, 50 Hz	G 1/4	G 1/4	7	(L/min) 1250	
K- 07 15 00 14	24 V DC	G 1/4	G 1/4	7	1250	