

# K-WV 3/2 5/2 NAMUR LB FR

3/2- and 5/2-way spool valves with NAMUR style interface and combined spring return

**HANSA FLEX**

## Properties

<b>Media</b>	Air, neutral gases (filtered)
<b>Working pressure</b>	1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22)
<b>Operating temperature</b>	-20 °C to +50 °C
<b>Connection 1 - 3</b>	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
<b>Port 1/3 + 5</b>	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
<b>Electrical connection</b>	Plug connector PG 9
<b>content of delivery</b>	Plug connector PG 9, conversion plate, screws and seal
<b>Power input</b>	3 W=5 VA~
<b>Housing</b>	Anodised aluminium
<b>Slider</b>	Stainless steel
<b>Sealant</b>	NBR



## Note

Further information on request

## Description

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function.

Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

Item					
Identification	Voltage	Port 1	Port 3 - 5	DN	Flow rate (L/min)
K- 07 15 00 15	230 V, 50 Hz	G 1/4	G 1/4	7	1250
K- 07 15 00 16	24 V DC	G 1/4	G 1/4	7	1250